



**PROEURO TECH<sup>®</sup>**  
PERFORMANCE SOUND

**PRO-999**

# TRUE DIVERSITY UHF WIRELESS MICROPHONE



## Technical Data

- Frequency range: UHF A: 694-703 MHz  
B: 748-758 MHz
- RF output power: 9.5mW
- Frequency Stabilization:  $\leq \pm 30$ ppm
- Dynamic Range:  $> 100$ dB
- Total Harmonic Distortion:  $< 0.5\%$
- Frequency Response: 40Hz~15KHz $\pm 3$ dB
- Ideal distance: 100m.
- Standard 19-inch mounting dimensions.
- Designed for stage and other high-class occasions.
- Power supply: AC 220V/50Hz





**PROEURO TECH<sup>®</sup>**  
PERFORMANCE SOUND

**ER-3800**

**NEW WIRELESS SERIES**

**new**



## PROFESSIONAL UHF WIRELESS MIC SYSTEMS

**14650 LITHIUM BATTERY**

14650 Lithium Battery

### Technical Data

- Frequency range: UHF A: 694-703 MHz  
B: 748-758 MHz
- RF output power: 9.5mW
- Frequency Stabilization:  $<\pm 30\text{ppm}$
- Dynamic Range:  $>100\text{dB}$
- Total Harmonic Distortion:  $<0.5\%$
- Frequency Response:  $40\text{Hz}\sim 15\text{KHz}\pm 3\text{dB}$
- Audio Output Level: Balance 400mV  
Unbalance 400mV
- Standard 19-inch mounting dimensions.
- Designed for stage and other high-class occasions.
- Power supply: AC 220V/50Hz



Audio  
Reference  
Companding





**PROEURO TECH®**  
PERFORMANCE SOUND

**CB-900**

# PROFESSIONAL UHF WIRELESS MICROPHONE



- จอแสดงผล TFT
- มี ECHO ให้เลือก 3 แบบ
- ตั้งความถี่ได้ 2 X 32Channel



LED screen

**Long press:** Power ON/OFF

**Short press:** ECHO adjust

## Technical Data

- Frequency range: UHF A: 694-703 MHz(32CH) B: 748-758 MHz(32CH)
- RF output power: 9.5mW
- Frequency Stabilization:  $<\pm 30\text{ppm}$
- Dynamic Range:  $>100\text{dB}$
- Total Harmonic Distortion:  $<0.5\%$
- Frequency Response:  $40\text{Hz}\sim 15\text{KHz}\pm 3\text{dB}$
- Audio Output Level: Balance 400mV Unbalance 400mV
- Fashion TFT screen mini receiver
- Designed for stage and other high-class occasions
- Power supply: DC 12V



Audio  
Reference  
Companding





**PROEURO TECH**  
PERFORMANCE SOUND

# WIRELESS CONFERENCE SYSTEM

## HOST USE INSTRUCTIONS

The system adopts a combination of teaching character and analog circuit technology, with a high fidelity circuit design that can produce high-quality audio effects. Use up to 20 sets simultaneously in the same environment. Each set can support multiple chairpersons and 256 delegates to use. It has multiple conference modes and conference recording function. The usage distance is 60-100 meters, depending on the usage environment!



มอก.1195-2536  
บริษัท โปรยูโร เทค จำกัด



### RECEIVER PARAMETERS

Usage frequency	748-758MHz
Data frequency	410-470MHz
Modulation method	FM
Frequency response	50Hz to 15KHz
Signal source sensitivity	-104db

Sound output size	6.35 mixed output 250mV
Karon balanced output	140mV
Distortion	<1%
Signal to noise ratio	≥ 90db

**GR-5200**





**PROEURO TECH**  
PERFORMANCE SOUND

# PROFESSIONAL WIRELESS MICROPHONE

The wireless microphone is applied in concerts,  
band performances, personal exercises, band exercises.  
Wind music wireless microphone, suitable for all kinds of brass instruments such  
as trumpet, large, horn, trombone.



## KM-D300



มอก. 62368  
เล่ม 1-2563  
บริษัท โปรยูโร เทค จำกัด

### PARAMETERS

Frequency range	Channel A: 694-703 MHz Channel B: 748-758 MHz
Number of channels	Dual channel
Maximum deviation	+ 15KHz
In the letter	exercise than >100dB
Comprehensive distortion	less than 0.02%
Frequency stability	F+ 0.03%
Audio response	+ 40 Hz-16 KHz
Dynamic range	>100dB
Rated working current	480 mA
Working temperature	-20 to +50 DEG C
Rated working current	150 mA
Power supply	AC 220V/50Hz







**PROEURO TECH**  
PERFORMANCE SOUND



# PROFESSIONAL WIRELESS MICROPHONE



มอก. 62368  
เล่ม 1-2563  
บริษัท โปรยูโร เทค จำกัด

## KM-D500



### PARAMETERS

Frequency range	Channel A: 694-703 MHz Channel B: 748-758 MHz	Frequency stability	F+ 0.03%
Number of channels	Dual channel	Audio response	+ 40 Hz-16 KHz
Maximum deviation	+ 15KHz	Dynamic range	>100dB
In the letter	exercise than >100dB	Rated working current	480 mA
Comprehensive distortion	less than 0.02%	Working temperature	-20 to +50 DEG C
		Rated working current	150 mA
		Power supply	AC 220V/50Hz





**PROEUREO TECH**  
PERFORMANCE SOUND



# PROFESSIONAL WIRELESS MICROPHONE



มอก. 62368  
เล่ม 1-2563  
บริษัท โปรยูโร เทค จำกัด

- ✓ STAGE PERFORMANCE
- ✓ BAR SINGING
- ✓ CONFERENCE SPEECH
- ✓ SCHOOL CLASSROOM
- ✓ FAMILY ENTERTAINMENT
- ✓ KTV



## KM-D900

Frequency range	Channel A: 694-703 MHz Channel B: 748-758 MHz
Number of channels	Dual channel
Maximum deviation	+ 15KHz
In the letter	exercise than >100dB
Comprehensive distortion	less than 0.02%
Frequency stability	F+ 0.03%

Audio response	+ 40 Hz-16 KHz
Dynamic range	>100dB
Rated working current	480 mA
Working temperature	-20 to +50 DEG C
Rated working current	150 mA
Power supply	AC 220V/50Hz





**PROEURO TECH**  
PERFORMANCE SOUND

# PROFESSIONAL WIRELESS MICROPHONE

STAGE PERFORMANCE  
BAR SINGING  
CONFERENCE SPEECH  
SCHOOL CLASSROOM  
FAMILY ENTERTAINMENT  
KTV



มอก.1195-2536  
บริษัท โปรยูโร เทค จำกัด

DUAL CHANNEL  
**NEW**



**Q-5**



Frequency range	Channel A: 694-703 MHz Channel B: 748-758 MHz
Number of channels	Dual channel
Maximum deviation	+ 15KHz
In the letter	exercise than >100dB
Comprehensive distortion	less than 0.02%
Frequency stability	F+ 0.03%

Audio response	+ 40 Hz-16 KHz
Dynamic range	>100dB
Rated working current	480 mA
Working temperature	-20 to +50 DEG C
Rated working current	150 mA
Power supply	AC 220V/50Hz





**PROEURO TECH**  
PERFORMANCE SOUND



# PROFESSIONAL WIRELESS MICROPHONE Q-8



มอก. 62368  
เล่ม 1-2563  
บริษัท โปรยูโร เทค จำกัด



**CONSTANT FREQUENCY DISTANCE**  
**ANTI-INTERFERENCE DISTANCE**

## PARAMETERS

Frequency range	Channel A: 694-703 MHz Channel B: 748-758 MHz
Number of channels	Dual channel
Maximum deviation	+ 15KHz
In the letter	exercise than >100dB
Comprehensive distortion	less than 0.02%
Frequency stability	F+ 0.03%
Audio response	+ 40 Hz-16 KHz
Dynamic range	>100dB
Rated working current	480 mA
Working temperature	-20 to +50 DEG C
Rated working current	150 mA
Power supply	AC 220V/50Hz





**PROEURO TECH®**  
PERFORMANCE SOUND

## KB-C22

- ไมค์ลอย UHF
- มีเอฟเฟกต์ให้เลือก ECHO
- ตั้งช่องความถี่ได้ 34 ช่อง (2\*17 ช่อง)



Frequency set  
**Long press**  
Power ON/OFF  
**Short press**  
ECHO adjust



Powered by **LITHIUM BATTERY** Inside

**PROFESSIONAL MINI WIRELESS MICROPHONE**

### Technical Data

- Frequency range: UHF A: 694-703 MHz(17CH)  
B: 748-758 MHz(17CH)
- RF output power: 9.5mW
- Frequency Stabilization:  $<\pm 30\text{ppm}$
- Dynamic Range:  $>100\text{dB}$
- Total Harmonic Distortion:  $<0.5\%$
- Frequency Response:  $40\text{Hz}\sim 15\text{KHz}\pm 3\text{dB}$
- Audio Output Level: Unbalance 400mV
- Fashion mini receiver
- Designed for high-class occasions





**PROEURO TECH®**  
PERFORMANCE SOUND  
**PRO-777**

**UHF** PROFESSIONAL  
WIRELESS MICROPHONE



- using UHF wireless microphone special frequency, without interference from other industrial frequency.
- PLL digital frequency synthesis technology, provides up to 200 selected working channel, realize the simultaneous use of multiple machines.
- use infrared frequency synchronization technology, the transmitter operation is simple and convenient.
- In the transmitter power adjustable. When outdoor use, the choice of high power, the use of distance far, in the classroom or KTV occasions when using low power, can reduce the interference, save battery.
- In the pilot data control technology, effectively prevent the impact of radio frequency interference and other acoustic transmitter switch machine.
- In the transmitter uses 2 1.5V/AA batteries power supply, battery used for a long time, more convenient maintenance.
- with balanced and unbalanced audio output, convenient connection and various audio equipment.
- In the receiver can display parameters of the transmitter, which is convenient for monitoring.
- In the transmitter is made of high strength alloy materials, durable.

#### Wireless Receiver

##### PRO-777

- In the frequency range: Channel A : 694-703 MHz  
Channel B : 748-758 MHz
- Number of channels: Dual channel
- maximum deviation: + 15KHz
- In the letter: exercise than >100dB
- comprehensive distortion: less than 0.02%
- frequency stability: + 0.03%
- audio response: + 40 Hz-16 KHz
- dynamic range: >100dB
- rated working current: 480 Ma
- working temperature: -20 to +50 DEG C
- rated working current: 150 mA
- Power supply: AC 220V/50Hz

#### Handheld transmitter

##### PRO-777A / PRO-777B

- Carrier frequency: Channel A : 694-703 MHz  
Channel B : 748-758 MHz
- maximum deviation: + 15KHz
- In the letter: exercise than >100dB
- comprehensive distortion: less than 0.02%
- frequency stability: + 0.03%
- audio response: + 40 Hz-16 KHz
- dynamic range: >100dB
- Power: 8.5mW